

CRC COCKPIT MATT

Ref.: 10299

1. GENERAL DESCRIPTION

Cleans and renovates plastics and rubbers.

A combination of mild, quickly evaporating solvents and stable, inert polymers which leave a non-staining, water-repellent film. CRC Cockpit Matt forms a protective barrier against colour fading and hardening caused by the penetration of ozone, U.V. rays and oxygen.

2. FEATURES

- Cleans plastic and rubber.
- Polishes dashboards, bumpers, spoilers, vinyl roofs, upholstery, etc.
- · Removes stains and tar from car interiors.
- · Renovates car interiors.
- Forms a clear, inert, non-brilliant, water-repellent film.
- Leaves a fresh fragrant, orange smell.
- Its formula, without silicones, makes it possible to perform paint jobs on the surface afterwards.
- Harmless to the rubbers and plastics usual applied in the cars interior. Test on a small area before using on very sensitive plastics, adhesive mounted or stressed parts.
- Aerosols are equipped with the 360°C (upside-down) spray valve for added convenience.
- Aerosols are pressurised with high purity CO₂, giving an active product content of over 97%.

3. APPLICATIONS

- Dashboards
- Vinyl tops
- Bumpers
- Spoilers
- Vinyl upholstery parts
- Rubber mats
- Chrome

4. DIRECTIONS

- For large surfaces :
 - spray a light even film on the surface, and spread out immediately with a lint-free cloth.
- · For small surfaces:
 - spray the product first on a lint-free cloth and then apply to the surface.
- Repeat application if necessary.
- · Removal: by CRC Quickleen.
- Do not use on energised equipment.
- A safety data sheet (MSDS) according EU directive 93/112 is available for all CRC products.



CRC.



TECHNICAL DATA SHEET 2/2

CRC COCKPIT MATT

Ref.: 10299

5. TYPICAL PRODUCT DATA (without propellant)

Appearance : colourless liquid

Specific gravity @ 20°C : 0,66

Distillation range (solvent) : 40-65°C

Flash point (solvent) : < 0°C

PH : neutral

Dry film properties

Appearance : colourless film (non-shining)

Specific gravity @ 20° C : 0,86 Flash point (open cup) : > 160° C Auto-ignition temp. (in air) : > 250° C

6. PACKAGING

aerosol: 12 x 400 ml

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Version : 10299 03 0998 02 Date : 12 July 2004



